

Colorguard NFR is a **Boltaflex** vinyl performance fabric featuring our industry-leading **PreFixx** protective finish. Formulated without phthalates and fire retardants (FR), **Boltaflex** *Colorguard NFR* supports the growing trend towards eco-friendly solutions in contract design.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment

End-Use Applications

- Office Furniture
- Contract Seating
- Dining Seating
- Medical Furnishings
- Lobby furnishings & millwork
- Spas & Health Clubs

Physical Specifications

Weight (CFFA-700d)	36 oz/lin yd [24 oz/yd ²]
Weight, Metric (CFFA-700d)	1,021 g/lin m [680 g/m ²]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Polyester Jersey Knit
Roll Size	30 lin yd [27 lin m]
Emboss Level	Medium
Shipping Weight/ Roll	76 lb [34 kg]

Flame, Smoke & Toxicity

Meets or exceeds the following:	• Cal AB 2998
	• Cal Tech 117-2013 Sec 1
	NFPA 260 Class 1
	UFAC Fabric, Class 1
	BIFMA - Class A
	IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
	IMO Part 8 Upholstered Furniture 3.2 Propane Flame

Performance Features

Protective Finish	PreFixx
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	3 Warp, 3 Fill
Tensile Strength #, min (CFFA-17)	110 Warp, 85 Fill
Tack Strength #, min (CFFA-14)	60 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	25 Warp, 25 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Fungal Resistance (ASTM-G-21)	Pass
Bacterial Resistance (AATCC 147)	Pass
Bacterial Resistance (AATCC 100)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Compatible with Disinfectants	Yes. See Chem Resistance Tech Bulletin for more information.
Bleach-Safe	Yes, 10% Bleach Solution
Resistance to Sulfide Stain (ASTM D1712)	Yes
Oil Resistance (CFFA-13)	Yes
Urine Resistance (AATCC-6)	Yes

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.