

VINYL TEX

VINYL COATED POLYESTER FABRICS

PRODUCT SPECIFICATIONS

	10oz	14oz	18.5oz	F/R 18.5oz	22oz
Total Weight oz/yd² FS 191-5041			18.5oz/yd ²		
Fabric Type			Polyester Woven		
Thread Count (Warp x Fill)			18 x 17 (1000Dx1300D)		
Tensile Strength, Grab FS 191-5100 (lbs.)			Warp 410 Fill 410		
Tensile Strength, Strip FS 191-5102 (lbs.)			Warp 300 Fill 300		
Tear Strength, Tongue FS 191-5134 (lbs.)			Warp 100 Fill 315		
Adhesion FS 191-5970 (bs./inch)			Warp 12 Fill 10		
Abrasion Resistance FS 191-5306			400 Cycles		
Hydrostatic Resistance FS 191-5512 (bs./inch ²)			At Least 600 PSI		
Cold Crack FS 191-5874			-40° F		
High Temperature Resistance FS 191-5872			180° F (Does Not Block)		
U.V. Resistance Weather-O-Meter			Not Excessive Fading After 300 Hours		
Flame Resistance / Vertical NFPA 701, Large & CSFM			N/A		

ALL COLORS OFFERED IN 18.5oz

Call for color availability for 10oz, 14oz, F/R 18.5oz & 22oz

The information and recommendations contained herein are offered as a service to our customers, but are not intended to relieve the user from his responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of other materials. The information and recommendations provided herein were believed to be accurate at the time of preparation or obtained from sources believed to be generally reliable. However, we make no warranty concerning their accuracy and will not be liable for claims relating to any party's use of or reliance on information or recommendations contained herein, regardless of whether it is claimed that the information or recommendations are inaccurate, incomplete or otherwise misleading.